




MODEL SV60 E



-  Premium quality
-  Power output range 320-330 Wp
-  100% EL testing
-  Mechanical load up to 5400 Pa
-  Low weight
-  Module efficiency up to 19,88 %
-  Positive power tolerance -0/+4,9 W
-  Made in Europe
-  IEC EN 61215
IEC EN 61730-1, -2
-  IEC EN 62716 Ed.1
-  IEC EN 61701
-  IEC TS 62804-1
(PID resistance)

Warranty:

- 10** years manufacturing defects
- 12** years limited, 90% output power
- 25** years limited, 80% output power



Electrical parameters at Standard Test Conditions (STC)				
MODEL		SV60-320 E	SV60-325 E	SV60-330 E
Peak power P_{MPP}	[W]	320	325	330
Peak power tolerance	[W]		-0/+4,9	
Short circuit current I_{SC}	[A]	10,15	10,24	10,30
Open circuit voltage V_{OC}	[V]	40,02	40,14	40,50
Rated current I_{MPP}	[A]	9,55	9,66	9,74
Rated voltage V_{MPP}	[V]	33,64	33,67	33,88
Current and voltage tolerance	[%]		± 3	
Module efficiency	[%]	19,28	19,58	19,88

STC: 1000W/m² irradiance, 25 °C cell temperature, AM1, 5 g spectrum according to EN 60904-3
Average relative efficiency reduction of 3,4 % at 200 W/m² according to EN 60904-1

Electrical parameters at Nominal Operating Cell Temperature (NOCT)				
MODEL		SV60-320 E	SV60-325 E	SV60-330 E
Peak power P_{MPP}	[W]	233,8	236,7	240,1
Peak power tolerance	[W]		-0/+4,9	
Short circuit current I_{SC}	[A]	8,15	8,22	8,27
Open circuit voltage V_{OC}	[V]	36,8	36,9	37,2
Rated current I_{MPP}	[A]	7,64	7,74	7,80
Rated voltage V_{MPP}	[V]	30,6	30,6	30,8

NOCT: module operating parameters at 800 W/m² irradiance, 20 °C ambient temperature, 1 m/s wind speed

MECHANICAL DATA	
Dimensions (H x W x D)	[mm] 1660 x 1000 x 35
Weight	[kg] 18,9
Solar cells	60 cells, monocrystalline Si (PERC), 157 x 157 mm +/- 2mm
Cells encapsulation	Ethylene vinyl acetate (EVA)
Front	Tempered solar glass, 3,2 mm
Back	Composite polyester Film
Frame	Anodized aluminium frame with twin-wall profile and drainage holes
Junction box	IP67 with 3 Bypass diodes,
Cable and connectors	Solar cable 4 mm ² , length 1200 mm

NOTE: For extended models, SV60 E YYY, voltages and currents can vary where YYY is optional based on the chosen YYY variant (YYY = letter(s), F for black frame, B for silver frame and black backsheet, BC for full black module)

OPERATING CONDITIONS		
Temperature range	[°C]	-40 to +85
Maximum system voltage	[V]	1000
Max. series fuse rating		15A
Limiting reverse current		15A
Maximum surface load capacity		5400 Pa (Snow load)
Resistance against hail		Max. diameter of 25 mm with impact speed 23 m/s

THERMAL CHARACTERISTICS		
Temperature coefficient of P_{MPP}	[%/K]	-0,42
Temperature coefficient of I_{SC}	[%/K]	0,05
Temperature coefficient of V_{OC}	[%/K]	-0,33

